

*Feature:

- HALED patent optics design, similar to halogen light effect
- Easy and quick installation
- PF>0.8, flicker free, follows new ErP
- Dimmable or dim to warm halogen function by triac dimmer
- CRI 95, R9>70
- Low UGR
- Peak luminous intensity 1050cd (24°) / 800cd (36°)
- Metal appearance, excellent heat dissipation
- Lifespan 40000 hrs, 5 years warranty
- High energy efficiency



CE RoHS ErP




Ø 68mm



Technical data

Part No.	Type of installation		
CTCA3406WKW/ N/ B	Recessed		
Electrical specifications			
Wattage (W)	6W	Power factor	0.8
AC input voltage (V)	AC200V-240V	Current	30mA
Frequency (Hz)	50/60Hz	DC output voltage (V)	
Flicker metric PST	0.023	Stroboscopic effect metric SVN	0.25
Total harmonic distortion (THD)	27%	Dimmable	Dim to warm
Max. no. of lamps on B16A circuit breaker	420	Max. no. of lamps on C10A circuit breaker	260
Max. no. of lamps on C16A circuit breaker	420		
Photometric specifications			
Color temperature (CCT)	2700K-2100K	CRI/ R9	95/ >70(Min.)
Chromaticity coordinate (x/ y)	0.459/ 0.412	Standard deviation of colour	≤5 SDCM
Useful luminous flux (lm)	400lm ± 5%	Luminous efficiency (lm/W)	66lm/ W
UGR	≤19		


Photometric Information



EAN	Colour	Beam angle	Peak Luminous intensity		
41108	Matt White	24°	1050cd		
41113	Stain Nickel	24°	1050cd		
41201	Matt Black	24°	1050cd		
41030	Matt White	36°	800cd		
41058	Stain Nickel	36°	800cd		
41196	Matt Black	36°	800cd		

Mechanical specifications			
Housing material	Aluminium	Housing Colour	Matt White / Stain Nickel / Matt Black
Optical cover/ lens material	AlReflector+PC+Glass	Length/ diameter	85mm
Height	55mm	Hole size	68mm
Product weight	200g		
Lifespan			
Number of switching cycles	100,000-	L70/B50 service life at 25°C	50,000 hrs
L80/B10 service life at 25°C	40,000 hrs	L90/B10 service life at 25°C	20,000 hrs
Warranty	5 Years		
Application parameters			
Working temperatuer range	-20~+50°C	Storage temperature range	-20~+70°C
Package			
Individual package length	105mm	Shipping box heigth	550mm
Individual package height	68mm	Shipping box height	166mm
Individual package width	105mm	Shipping box width	240mm
Gross weight (single item)	220g	Packaging unit	20pcs
Driver	Internal	Gross weight (Shipping box)	4.8kgs

Technical Drawings (mm)



Package



85*55mm



105*105*68mm




550*20*166mm(20PCS)

Cautions:

- Power off before replacement
- Do not in violation of any fire regulations when using
- Consult competent electricians for technical support
- If the supply cord is damaged, it shall be exclusively replaced by the manufacture or his service agent o similar qualified person in order to avoid a hazard

Installation /Mounting:

Please read the entire instruction manual before using the product and reserve it for future reference. We reserve the right for any error in text or image and any necessary change made to technical data. If you have any question regarding technical problems, please contact our Customer Services.



For non replacable lightsources. The light source of this luminaire is not replaceable; when the light source reaches its end of life, the whole luminaire shall be replaced"